



FEATURING:

- 7" COLOUR LCD MONITOR
- 130° WIDE ANGLE
- IP67 WATERPROOF CABLES
- O-RING, THREADED CONNECTIONS
- 8G SHOCKPROOF
- SUNVISOR + AUTOMATIC PANEL LED ACTIVATION AT NIGHT *

CAMERA PRODUCT SPECIFICATIONS

	RDC-002	RDC-003	RDC-006
IMAGE DISPLAY	Colour	Colour	Colour
LOW LIGHT RATING	0.05 Lux	0 Lux	0 Lux (LED ON)
INFRARED LED'S	18	9	9
PIXELS	297,984	297,984	287,984
RESOLUTIONS	420 TV Lines	420 TV Lines	420 TV Lines
AUDIO	Yes	No	No
WEATHER RATING	IP67	IP67	IP67
OPERATING TEMP	-25° / +50° (c)	-25° / +50° (c)	-20°C~70°C
SHOCK RATE	8g	8g	8g
VIEW AREA	130°	130°	180°
WARRANTY	1 Year	1 Year	1 Year

MONITOR PRODUCT SPECIFICATIONS

	RDV-LCD
DISPLAY	7" Pure Colour LCD
CAMERA INPUTS	2
MIRROR IMAGE	Yes
RESOLUTION	480 x 3(RGB) x 234
OPERATING TEMP	-10° / +60° (c)
SHOCK RATE	8G
AUDIO	Yes
INPUT VOLTAGE	12V
DIMENSIONS	200 mm (w) 133 mm (h) 38 mm (L)
WARRANTY	1 Year



RDC-002



RDC-003



RDC-006



RDH-5M
RDH-10M
RDH-15M
RDH-20M
RDH-25M



RDV-QUAD

FEATURING:

- 7" COLOUR LCD MONITOR
- DISPLAYS SINGLE, DUAL, TRIPLE, QUAD IMAGE OR PIP IMAGES
- VOLUME AND MIRROR FUNCTION FOR EACH CAMERA CAN BE SEPARATELY SET UP
- CAMERA NAMES CAN BE SET UP
- FOUR TRIGGER WIRES FOR CAMERAS. SEPARATE TRIGGERS.
- AUTO SCANNING AND TIMED IMAGE SWITCH
- BACKUP DISTANCE GRID & LEFT / RIGHT-TURNING INDICATOR ARROW AVAILABLE

RDV-QUAD SPECIFICATIONS

DISPLAY	7" Pure Colour LCD	AUDIO	Yes
CAMERA INPUTS	4	INPUT VOLTAGE	12V - 32V
MIRROR IMAGE	Yes	DIMENSIONS	182 MM (w) 122 MM (h) 43 MM (L)
RESOLUTION	1440 (w) x 234 (h)	WARRANTY	1 Year
OPERATING TEMP	-10° / +65° (c)		
SHOCK RATE	8G		

With the IP67 waterproof threaded connections, O-Ring seal and external protective boot, moisture and salt is kept out of the harness.

DISTRIBUTED BY:



1-888-397-2253
1-888-EZSCALE
www.ezscale.com